

POWEROLL 15_s

The **POWEROLL 15** is our best selling 4ft wide cricket wicket roller, suitable for all grounds rolling needs. Like all other cricket rollers in the range this machine has been designed with driver comfort, ease of use and efficiency in mind. Power steering ensures that very little input from the driver is needed. The low un-ballasted and high-ballasted weight makes this machine ideal for all year use if required. For local authorities wishing to use 1 machine on several grounds, this cricket wicket roller can be transported with-in the 3.5 tonne weight limit (without ballast) subject to the vehicles specifications, on an 8 feet bed trailer. Designed to produce similar ground pressure on both rollers and each side of the machine for optimum results. For machines to be left outside, a heavy-duty fitted PVC cover is available.



Features and specifications:

- Rolling width of 48 inch (1.22m).
- Power steering as standard.
- Weight 1,100kg empty up to 2,300kg full (excluding driver).
- Ground pressure - min. 137kg per 1 ft and max. 287kg per 1 ft of roller.
- Speed range 0 - 5 mph - forward or reverse.
- Comfortable to drive and easy to operate.
- Low maintenance and running costs.
- Option of biodegradable hydraulic oil at extra cost.
- Hydrostat drive for a smooth, step-less increase of speed.
- No clutch, gearbox or foot pedals - simple lever control.
- Honda GX 340 engine as standard – Hatz diesel engine option.
- Low engine noise due to its under seat location.
- Machined and radiused edge rollers for optimum results.
- Easy entry and a raised driving position for improved visibility.
- Recently restyled, providing even better visibility close to the machines perimeters



Optional extras include:

Electric start Honda GX390 engine, drip tray, Hatz 1B40 diesel engine. Shaped PVC machine cover, sun canopy, scrapers, Roll over bar.

(Product launch - restyled machine Saltex 2009 – left)

DON'T JUST ROLL IT...

POWEROLL IT!

POWER Precision & Fabrication Ltd.

01822 832608

website: www.poweroll.com